

10-Device Static USB Charging Cabinet - Desk Mounted for Tablets and USB devices up to 11" – Horizontal

- **The Lyte 10 Single Door Tablet USB** charges 10 tablets or devices up to 11" screen size – tablets, smartphones, mobile phones and handheld USB devices (including protective cases) via a 10 port USB A Hub.
- **With individual device compartments** that store devices horizontally within a compact footprint.
- **This unit delivers high-speed charge** at the optimum rate.
- **Equivalent to 10 x 12W USB A Charging Ports** saving you space and power consumption, replacing extension cables and power sockets with one cable into the wall
- **It never overcharges** as it detects when the device battery is full providing trickle charge.
- **Provides maximum security & safety** with a dual point locking system and separate lockable power compartment.
- **With Support for Life with Lifetime Warranty** (5 years electrical), shipped fully assembled.



	Code/SKU	Number of devices can hold	Unit Dimensions	Device Compartment Size
Lyte 10 SD Tablet USB	LYTE10SDTABUSBBL	10	W325 x D540 x H360 mm 12.8" x 21.2" x 14.2"	W235 x D305 x T30mm 9.2" x 12" x 1.2"

IMPORTANT NOTE: CHECK ACTUAL DEVICE SIZE, INCLUDING POWER CABLE FOR COMPATIBILITY WITH DEVICE COMPARTMENT SIZE. IF IN DOUBT PLEASE CONTACT LAPCABBY FOR CONFIRMATION

Materials	18mm MFC and 1.6mm powder coated steel			
Safety	All products are tested to the highest standard Europe: EN 62368-1:2014 Safety testing is a high priority to LapCabby. We don't release any products unless the unit has been completely certified including electrics, materials, construction and components. Leading safety testing house we test the normal operating conditions of the product but also for faults, misuse, temperature, fire risk, electric shock and injury			
Testing certifications	Safety tested to the highest level			





Inset door handles.



Lock supplied with 6 plate lever activation system.



Strong MFC cladding.



Non-marking feet.



1.6mm grey steel fixed shelves with ventilations.



Well placed vents to the rear and base.



Front door opens 270 degrees.



IEC power cable into the mains.



Isolated power compartment for electrical safety.

